WELD-PAK® 90i FC

COMPACT VERSATILITY



KEY FEATURES

The WELD-PAK® 90iFC welding machine is a lightweight and ultra-portable welder that connects to 120 volt power. This machine is an excellent choice for Flux-Cored welding. The intuitive user interface, easy setup, and full list of accessories permits welding in no-time.

VERSATILE PERFORMANCE

- Unit capable of flux-cored welding.
- Flux-cored welding up to 120
 Amps at a maximum thickness of 1/4".

EASY TO USE

- · Simple two-knob control for wire speed and voltage
- · Fast toolless drive roll changeovers
- Fast-feed wire loading switch to assist in loading welding wire.

COMPACT DESIGN

- · Lightweight and portable at 15 lbs
- · Conveniently plugs into household 120 volt power.

Processes »

Flux-Cored

Applications »

- Automotive
- > Home
- > Construction
- › Lawn and garden
- > Powersports
- › Maintenance and Repairs

Output »





Input »





Product Number »

K5255-1 WELD-PAK® 90i FC



ULTRA PORTABLE WIRE FEED WELDER

- 1. Over-the-shoulder carrying strap for transporting welder
- 2. Voltage and wire-speed knobs with built-in indicators
- 3. Impact-resistant front protects controls and connectors
- 4. Vented front for pull through fan cooling
- 5. Built in thermal protection with LED indicator
- 6. Hard-wired welding gun connection, resists corrosion and provides maximum electrical connection.
- 7. 18 gauge metal case provides protection from the elements
- 8. Quarter-turn fixed-pressure wire spool tensioner for toolless welding wire changes
- 9. Drive tension adjustment knob
- 10. Knurled drive roll ensures positive solid and flux-cored wire feeding
- 11. Fast-feed wire loading switch to assist in loading welding wire.



USE WITH THESE LINCOLN WELDING WIRES

Process	Wire Dia. (in.)	24ga.	22ga.	20ga.	18ga.	16ga.	14ga.	12ga.	1/8"	10ga.	3/16"	1/4"
Flux-Cored Welding – Steel	.030 .035					IELD® NR®-2 IELD® NR®-2			SP SP			MP MP

SP - Single Pass MP - Multiple Pass

DRIVE ROLLS						
Product Number	Wire Diameter inches (mm)	Process				
KP4364	.030035 (0.9-1.1)	Flux-cored				

WHAT'S INCLUDED

RECOMMENDED ACCESSORIES

Gun

- · Attached WP100L gun with 6 ft. (3.0m) cable.
- · .030 in. (0.9 mm) contact tip (KH711)
- · .035 in. (1.2 mm) contact tip (KH712)
- Gasless nozzle for Innershield® welding (KH726)
- · Drive roll for flux-cored welding

Other

· Instruction manual



GENERAL OPTIONS

Welding Cart

Full-featured cart is designed to store and transport a welder, 80 cubic foot gas cylinder, welding cables and accessories. Includes an angled top shelf for easy access to welder controls, a lower tray for added storage space, a sturdy handle also used as a convenient cable wrap hanger. **K2275-3**

WELD-PAK ° 90i FC- SPECIFICATIONS

Product Number	Input Power	Rated Output Current/	Input Current @	Output	Wire Feed Speed	HxWxD	Net Wt
	Voltage/Phase/Hertz	Voltage/Duty Cycle	Rated Output	Range	ipm (m/min)	in (mm)	lb (kg)
K5255-1	120/1/60	90A/21V/30%	20A	20-120 AMP	20-200 (51-508 cm/min)	13.6 x 8.9 x 18.1 (345 x 224 x 460)	15 lbs. (6.8 Kg)

For best welding results with Lincoln Electric* equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more details.

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company* is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change — This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectricretail.com for any updated information.

All trademarks and registered trademarks are the property of their respective owners.